



P - Type "Quick Lock" Triple Row

<p>Plug Housing (load with Female Contact)</p> <p>Order Code Housing: PCF-3xx-P635/X</p>	<p>Clutch Housing (load with Male Contact)</p> <p>Order Code Housing: PCC-3xx-P635/X</p> <p style="font-size: small;">For Panel cut out and thickness dimension please order product drawing</p>
<p>Female Contact</p> <p>Order Code: PCF-999/xx-P635-99 MOQ: 10K / reel</p>	<p>Male Contact</p> <p>Order Code: PCM-999/xx-P635-99 MOQ: 10K / reel</p>

Fully Shrouded Header

<p>-THT- Female straight (top entry)</p> <p>Order Code: PCS-3xx-PF635-99/X</p>	<p>-THT- Male straight (top entry)</p> <p>Order Code: PCS-3xx-PM635-99/X</p>
--	--

Specifications

Current rating	11 A	Voltage rating	600 V AC max.	Contact material	Copper Alloy
Insulation resistance	1000 MΩ min.	Withstanding voltage	1000 V AC	Insulator material	PA66 UL 94V-0 & V-2
Contact resistance	20 mΩ max.	Operating temperature	-55°C to +105°C	PCB thickness	1.60mm

How to order

PC X - x xx - X 635 - 99 / X

<p>Type</p> <p>C = Clutch F = Female M = Male S = Straight</p>	<p>Rows</p> <p>3 = triple row</p> <p><i>if Crimp Contact:</i> 9</p>	<p>Nbr of Contacts</p> <p>P, PF & PM – Execution: 06, 09, 12 & 15</p> <p><i>if Crimp Contact:</i> 99/10 = for AWG 12~14 99/16 = for AWG 16~20 99/19 = for AWG 18~22</p>	<p>Execution</p> <p>P = P - Type PM = P - Type male PF = P - Type female</p> <p style="font-size: small;">for details see above dwg's</p>	<p>Plating</p> <p>99 = Tin (leadfree)</p> <p style="font-size: small;">other platings on request</p>	<p>Color Option</p> <p>N = nature (UL 94V-2) W = white (UL 94V-0)</p> <p style="font-size: small;">PF & PM Execution if polarizing is requested: NP = nature (UL 94V-2) WP = white (UL 94V-0)</p>
---	--	--	---	--	--