



DÉTAIL C
ECHELLE 10 : 1

Mechanical data		Specifications	
Contact (RoHS compliant)	Phosphor bronze	Electrical data	100 V RMS / 150V DC
Plating	Sn (leadfree) over Ni	Measuring voltage	> 600 V RMS
Insulator (RoHS compliant)	High temp plastic black UL 94 V-0	Breakdown voltage	< 20 mΩ
Temperature	Operating temp. - 40°C to +105°C	Contact resistance	> 5000 MΩ
	Processing temp. +250°C +0/-5°C	Current rating	1 A max., 100V
	for 20-40sec.	Capacitance	< 2 pF

<p>A3H Scale 5:1</p> <p>UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL TOLERANCES ISO 2768m</p>	<p>REV 4b</p>		<p>E-tec Interconnect</p> <p>"E-tec order code" PLU-044-H901-99</p> <p>"Production code"</p>	<p>Remark:</p>
	<p>patented</p>	<p>NAME DATE</p> <p>DRAWN sme 19.12.2018</p> <p>REV'D sme 07.05.2024</p> <p>CHK'D - -</p> <p>APPV'D sme 07.05.2024</p>		

