



DÉTAIL C  
ECHELLE 10 : 1

Mechanical data		Specifications	
Contact (RoHS compliant)	Phosphor bronze	Electrical data	100 V RMS / 150V DC
Plating	Sn (leadfree) over Ni	Breakdown voltage	> 600 V RMS
Insulator (RoHS compliant)	High temp plastic black UL 94 V-0	Contact resistance	< 20 mΩ
Temperature	Operating temp. - 40°C to +105°C	Insulation resistance	> 5000 MΩ
	Processing temp. +250°C ±0/-5°C	Current rating	1 A max., 100V
		Capacitance	< 2 pF
			for 20-40sec.

Compatible with Lynred Pico384-053 (Pico384+Gen2) and Pico160-054

<p><b>A3H</b> Scale 5:1</p> <p>UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS GENERAL TOLERANCES ISO 2768m</p>	<p>REV 4c</p>		<p><b>E-tec</b> Interconnect</p> <p>"E-tec order code" <b>PLU-044-H901-99</b></p> <p>"Production code"</p>	<p>Remark:</p>
	<p>NAME DATE</p> <p>DRAWN sme 19.12.2018</p> <p>REV'D sme 25.11.2024</p> <p>CHK'D - -</p> <p>APPV'D sme 25.11.2024</p>	<p>The information contained in this drawing is proprietary to E-tec Interconnect AG and shall not be reproduced or disclosed in whole or in part or used for any design or manufacture except when such user possesses direct, written authorization from E-tec Interconnect AG</p>		

